

## Granville FS-BX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville FS-BX 0W/30 is the very latest generation fully synthetic low viscosity engine oil. FS-BX offers excellent fuel efficiency and engine protection whilst meeting the requirements of soot control for those vehicles with engine exhaust after treatment devices fitted.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3  
 BMW: LL-04  
 MB: 229.51  
 Porsche: C30  
 VW: 504.00, 507.00, 503.00, 506.00 & 506.01  
 API: SN

### PRODUCT BENEFITS

- \* Low SAPS formulation
- \* Fully synthetic
- \* Excellent fuel efficiency

### PRODUCT USAGE

For vehicles where this grade and specification of engine oil is required.

### DIRECTIONS FOR USE

Use as specified by the vehicle manufacturer

### STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0793	5020618007937
5 Litre	0794	5020618007944
20 Litre	0795	5020618007951
199 Litre	0799	5020618007999



# Granville FS-BX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Amber oily liquid

**Odour** : Characteristic

**Solubility** : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	11.3
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.21
Pour Point	ASTM D97	°C		-42	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			59.17
Density	ASTM D792	@ 15°C			0.841

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

